



Preparing for the New Era of Laboratories

MATERIAL SAFETY DATA SHEET (MSDS)

According to regulation (EU) no.1907/2006

GIEMSA'S STAINING SOLUTION FOR MICROSCOPY

PRODUCT CODE : L-1212

CAS No : not applicable

FORMULA : not applicable

UN No : 1230

website : www.labotiq.net

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

GIEMSA'S STAINING SOLUTION FOR MICROSCOPY



MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product Name** : GIEMSA'S STAINING SOLUTION FOR MICROSCOPY
Synonyms : Azure eosin methylene blue Giemsa solution
CAS No. : not applicable
HS Code : 3212 9090
Chemical Formula : not applicable
Molecular Weight : not applicable
Product Code : L-1212
Brand : Labotiq
1.2 Manufacturer : Labotiq
Address : Jl.Terapi Raya AD2-Bumi Menteng Asri Bogor, Jawa Barat Indonesia – 16111
Website : www.labotiq.net
Email : labotiq.id@gmail.com
For information : Phone : (+62-251) 839110, 8311662, Fax : (+62-251) 83135710
Emergency number : +6281316894650
1.3 Application : Laboratory chemicals, Manufacture of substances, General Chemical reagent

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids, (Category 2)	H225: Highly flammable liquid and vapor.
Acute toxicity, (Category 3)	H301: Toxic if swallowed.
Acute toxicity, (Category 3)	H331: Toxic if inhaled.
Acute toxicity, (Category 3)	H311: Toxic in contact with skin.
Specific target organ toxicity - single exposure, (Category 1), Eyes, Central nervous system	H370: Causes damage to organs.

For the full text of the H-Statements mentioned in this Section, see Section 16

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapor.

H301 + H311 + H331

Toxic if swallowed, in contact with skin or if inhaled.

H370

Causes damage to organs (Eyes, Central nervous system).

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

GIEMSA'S STAINING SOLUTION FOR MICROSCOPY



MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

P233	Keep container tightly closed. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
Supplemental Hazard Statements	none
Reduced Labeling (<= 125 ml)	
Pictogram	



Signal Word	Danger
Hazard Statements	
H370	Causes damage to organs.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.

Precautionary Statements	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor. Supplemental Hazard Statements none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Azure eosin methylene blue Giemsa solution

3.2 Mixture

Component	Classification	Concentration
Methanol	Flam. Liq. 2; Acute Tox. 3; STOT SE 1;	>= 30 - < 50 %

CAS-No. 67-56-1 EC-No. 200-659-6 Index-No. 603-001-00-X Registration number 01-2119433307-44- XXXX	H225, H301, H331, H311, H370 Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	
1,2,3-Propanetriol(glycerin) (CAS No) 56-81-5 (EC no) 200-289-5	Not classified	50 – 75 %
GIEMSA'S STAIN (CAS No) 51811-82-6	Eye Dam. 1, H318 Acute Tox. 4 (Oral), H302 Aquatic Chronic 3, H412	0.01 - 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour).

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides
Combustible.

MATERIAL SAFETY DATA SHEET (SDS/MSDS)
GIEMSA'S STAINING SOLUTION FOR MICROSCOPY

MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

Pay attention to flashback.

Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures Immediately

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2

7.2 Conditions for safe storage, including any incompatibilities**Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

GIEMSA'S STAINING SOLUTION FOR MICROSCOPY



MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Appropriat engineering controls

General industrial hygiene practice.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

required

Full contact

Material: Viton®

Minimum layer thickness: 0,7 mm

Break through time: > 480 min

Material tested: Vitoject®

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0,7 mm

Break through time: 30 min

Material tested: Butoject® (KCL 898)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Form: liquid

Colour: dark blue

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

GIEMSA'S STAINING SOLUTION FOR MICROSCOPY



MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

Odour	odorless
Odour Threshold	No data available
pH	6,9
Melting point/freezingpoint	No data available
Initial boiling point and boiling range	No data available
Flash point	11 °C - closed cup
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	No data available
Vapour pressure	No data available
Vapour density	No data available
Density	No data available
Relative density	No data available
Water solubility	No data available
Partition coefficient: noctanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
Explosive properties	No data available
Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

Acids, Acid chlorides, Acid anhydrides, Oxidizing agents, Alkali metals, Reducing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - 260,68 mg/kg (Calculation method)

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

GIEMSA'S STAINING SOLUTION FOR MICROSCOPY



MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

Acute toxicity estimate Inhalation - 4 h - 8,07 mg/l - vapor (Calculation method)

Acute toxicity estimate Dermal - 781,51 mg/kg (Calculation method)

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture causes damage to organs.

Mixture causes damage to organs. - Eyes, Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

Methanol

Acute toxicity

Acute toxicity estimate Oral - 100,1 mg/kg (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3,1 mg/l - vapor (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300,1 mg/kg (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit Result: No skin irritation

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

GIEMSA'S STAINING SOLUTION FOR MICROSCOPY



MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

Remarks: (ECHA)

Remarks: Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Remarks: (ECHA)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative (OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute oral toxicity - Nausea, Vomiting Acute inhalation toxicity - Irritation symptoms in the respiratory tract.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

GIEMSA'S STAINING SOLUTION FOR MICROSCOPY



MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

Components

Methanol

Toxicity to fish

flow-through test LC50 - Lepomis macrochirus (Bluegill) - 15.400,0 mg/l - 96 h (US-EPA)

Toxicity to daphnia and other aquatic invertebrates

semi-static test EC50 - Daphnia magna (Water flea) - 18.260 mg/l - 96 h (OECD Test Guideline 202)

Toxicity to algae

static test ErC50 - Pseudokirchneriella subcapitata (green algae) - ca. 22.000,0 mg/l - 96 h (OECD Test Guideline 201)

Toxicity to bacteria

static test IC50 - activated sludge - > 1.000 mg/l - 3 h (OECD Test Guideline 209)

Toxicity to fish(Chronic toxicity)

NOEC - Oryzias latipes (Orange-red killifish) - 7.900 mg/l - 200 h

Remarks: (External MSDS)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1230

IMDG: 1230

IATA: 1230

14.2 UN proper shipping name

ADR/RID: METHANOL, SOLUTION

IMDG: METHANOL, SOLUTION

IATA: Methanol, SOLUTION

14.3 Transport hazard class(es)

ADR/RID: 3 (6.1)

IMDG: 3 (6.1)

IATA: 3 (6.1)

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

Further information

No data available

SECTION 15: Regulatory information

MATERIAL SAFETY DATA SHEET (SDS/MSDS)
GIEMSA'S STAINING SOLUTION FOR MICROSCOPY

MSDS Number : 0162

Date : Dec 13th, 2024

Version : 1.0

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Methanol

National legislation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

H2 ACUTE TOXIC

P5c FLAMMABLE LIQUIDS

22 Methanol

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information**Full text of H-Statements referred to under sections 2 and 3.**

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

National Fire Protection Association (U.S.A.):

Health: 2

Flammability: 3

Reactivity: 0

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Labotiq shall not be held liable for any damage resulting from handling or from contact with the above product.

Version : 1.0

Revision Date : December 13, 2024