



Preparing for the New Era of Laboratories

MATERIAL SAFETY DATA SHEET (MSDS)

According to regulation (EU) no.1907/2006

MAGNESIUM OXIDE LIGHT 96% Extrapure

PRODUCT CODE : O-5113

CAS No : 1309-48-4

FORMULA : MgO

UN No : Not Applicable

MATERIAL SAFETY DATA SHEET (SDS/MSDS)
MAGNESIUM OXIDE LIGHT 96% Extrapure

MSDS Number : 0212

Date : May 8th, 2025

Version : 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product Name** : MAGNESIUM OXIDE LIGHT 96% Extrapure
Synonyms : Calsinated Magnesia
CAS No. : 1309-48-4
HS Code : 2519 9040
Chemical Formula : MgO
Molecular Weight : 40,30 g/mol
Product Code : O-5113
Brand : Labotiq
1.2 Manufacturer : Labotiq
Address : Jl.Terapi Raya AD2-Bumi Menteng Asri Bogor, Jawa Barat Indonesia – 16111
Website : www.labotiq.net
Email : labotiq.id@gmail.com
For information : Phone : (+62-251) 839110, 8311662, Fax : (+62-251) 83135710
Emergency number : +6281316894650
1.3 Application : Laboratory chemicals, Manufacture of substances, General Chemical reagent

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture**
Classification according to Regulation (EC) No 1272/2008
Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008
- 2.2 Label elements**
Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008
- 2.3 Other hazards**
This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

- 3.1 Substances**
Synonyms : Calsinated Magnesia
Formula : MgO
Molecular weight : 40,30 g/mol
CAS-No. : 1309-48-4
EC-No. : 215-171-9
- 3.2 Mixture**
No components need to be disclosed according to the applicable regulations

SECTION 4: First aid measures

- 4.1 Description of first aid measures**
General advice
Consult a physician. Show this safety data sheet to the doctor in attendance.

MATERIAL SAFETY DATA SHEET (SDS/MSDS)
MAGNESIUM OXIDE LIGHT 96% Extrapure

MSDS Number : 0212

Date : May 8th, 2025

Version : 1.0

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given. For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Magnesium oxide, Not combustible. Ambient fire may liberate hazardous vapours

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus

5.4 Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

MAGNESIUM OXIDE LIGHT 96% Extrapure



MSDS Number : 0212

Date : May 8th, 2025

Version : 1.0

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Air and moisture sensitive.

Storage class

Storage class (TRGS 510): 13: Non Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Appropriat engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses.

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:Dermatril®

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

MAGNESIUM OXIDE LIGHT 96% Extrapure



MSDS Number : 0212

Date : May 8th, 2025

Version : 1.0

Splash contact
 Material: Nitrile rubber Minimum
 layer thickness: 0,11 mm
 Break through time: 480 min
 Material tested: Dermatril®

Respiratory protection

required when dusts are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.
 Recommended Filter type: Filter type P1

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Form: powder
	Colour: white
Odour	No data available
Odour Threshold	No data available
pH	No data available
Melting point/freezing point	Melting point/range: 2.852 °C - lit.
Initial boiling point and boiling range	3.600 °C at 1.013,25 hPa
Flash point	Not applicable
Evaporation rate	No data available
Flammability (solid, gas)	The product is not flammable
Upper/lower flammability or explosive limits	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	No data available
Density	3,580 g/cm ³
Water solubility	insoluble
Partition coefficient: noctanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

MAGNESIUM OXIDE LIGHT 96% Extrapure



MSDS Number : 0212

Date : May 8th, 2025

Version : 1.0

10.1 Reactivity

No data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

halogen-halogen compounds, acids, phosphorus pentachloride

Risk of explosion with:

powdered aluminium, perchlorates, powdered magnesium sulfur

10.4 Conditions to avoid

Air sensitive.

no information available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral: No data available

Inhalation: No data available

Dermal: No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

MATERIAL SAFETY DATA SHEET (SDS/MSDS)
MAGNESIUM OXIDE LIGHT 96% Extrapure

MSDS Number : 0212

Date : May 8th, 2025

Version : 1.0

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: OM3850000

Ingestion or inhalation of a large quantity may cause a feverish reaction and leukocytosis., Diarrhea
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Offer surplus and non-recyclable solutions to a licensed disposal company. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information**14.1 UN number**

ADR/RID: -

IMDG: -

IATA: -

14.2 UN proper shipping name

ADR/RID: Not dangerous goods

IMDG: Not dangerous goods

IATA: Not dangerous goods

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

MAGNESIUM OXIDE LIGHT 96% Extrapure



MSDS Number : 0212

Date : May 8th, 2025

Version : 1.0

14.3 Transport hazard class(es)

ADR/RID: -

IMDG: -

IATA: -

14.4 Packaging group

ADR/RID: -

IMDG: -

IATA: -

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user**Further information**

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

National Fire Protection Association (U.S.A.):

Health: 0

Flammability: 0

Instability : 0

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Labotiq shall not be held liable for any damage resulting from handling or from contact with the above product.

Version : 1.0

Revision Date : May 8, 2025